

Medium

BESTBOY EW S3

BESTBOYEW3

Extra wide fitting suede leather mid-cut

The Safety Jogger BESTBOY EW S3 is a versatile safety shoe with slip resistance, antistatic properties, and a removable footbed for customizable comfort. It offers sweat reduction, protection from falling objects, and penetration resistance.

| | |
|---------------|---|
| Upper | Suede Leather |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Midssole | Steel |
| Outsole | PU/PU |
| Toecap | Steel |
| Category | S3 / SRC |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.659 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |



BLK



SND




Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Forefoot energy absorption

Forefoot energy absorption reduces the impact of jumps or running on the body of the wearer.



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Assembly, Automotive, Construction, Industry, Logistics

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Suede Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 5.4 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 58 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 30.3 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 242 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 40 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.29 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.34 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.14 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.23 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 58.8 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 34 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 19.5 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 22.5 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.