



# SAFETY JOGGER

## PROFESSIONAL



Medium

## DUBLIN 02

**breathable uniform shoe for professionals**

The DUBLIN shoes are a blend of comfort and safety. With SR slip resistance, a removable footbed, SJ Grip, and breathable leather upper, they are perfect for professionals in various industries.

Upper	Nappa Leather
Lining	Microsuede
Footbed	SJ foam footbed
Outsole	PU/Rubber
Category	O2 / SRC
Size range	EU 39-48 / UK 6.0-13.0 / US 6.5-13.5 JPN 25-31.5 / KOR 255-315
Sample weight	0.429 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



BLK



**SRC slip resistance**  
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



**Breathable leather upper**  
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



**SJ Foam**  
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



**Removable insole**  
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



**Oxygrip / SJ Grip**  
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



### Solutions for every workplace

INDUSTRIAL   PROFESSIONAL   TACTICAL   TIGER GRIP

ENGINEERED IN EUROPE

www.safetyjogger.com

**Industries:**

Catering, Food &amp; beverages, Industry

**Environments:**

Dry environment, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Nappa Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	2.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	20.3	≥ 15
<b>Lining</b>	<b>Microsuede</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	55.9	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	447.4	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>PU/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	88.9	≤ 150
	Outsole slip resistance SRA: heel	friction	0.49	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.41	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.32	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.37	≥ 0.18
	Antistatic value	MegaOhm	17.2	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	41.6	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.