



SAFETY JOGGER

PROFESSIONAL



Light

JAMES OB

Sporty and ultra-light sneaker for him

The JAMES sporty and ultra-light sneakers offer unmatched comfort with a removable footbed, 3D mesh, and superior support.

Upper	Mesh
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Phylon/Rubber
Category	OB / SRA, E
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.330 kg
Norms	EN ISO 20347:2012



BLK



LGR



NAV



3D mesh
Three-dimensional produced distance mesh to provide increased moisture and temperature management.



Coolmax® lining
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:

Catering, Food & beverages, Medical

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Mesh			
	Upper: permeability to water vapor	mg/cm ² /h	1.4	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	15.5	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	28.9	≥ 2
	Lining: water vapor coefficient	mg/cm ²	231.3	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Phylon/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	81	≤ 150
	Outsole slip resistance SRA: heel	friction	0.48	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.45	≥ 0.32
	Outsole slip resistance SRB: heel	friction	N/A	≥ 0.13
	Outsole slip resistance SRB: flat	friction	N/A	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	34	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.