



Medium

## RUSH S3

**Fashionable safety shoe with a zipper on the side**

Safety Jogger's RUSH safety shoes offer supreme protection with a steel toecap and midsole. Antistatic, oil & fuel resistant, and breathable for comfort in various industries and environments.

Upper	Pull-up Leather, Textile
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SRC
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.712 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BRN




CAM




SND




**Breathable leather upper**  
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.




**Antistatic**  
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm




**Steel toecap**  
Robust metal support to protect the feet of the wearer against falling or rolling objects.



**Steel midsole**  
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



**Oil & fuel resistant**  
The outsole is resistant against oil and fuel.



**S3**  
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.

**Industries:**

Automotive, Cleaning, Construction, Logistics, Mining, Oil &amp; Gas, Industry

**Environments:**

Muddy environment, Uneven surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Pull-up Leather, Textile</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	3.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	33.2	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	51.9	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	415.5	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	127.3	≤ 150
	Outsole slip resistance SRA: heel	friction	0.28	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	46.4	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	28	≥ 20
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.