



# SAFETY JOGGER

## PROFESSIONAL



Light

## SUN OB SLP

SUNOBSLP

**Extremely comfortable, slip-resistant and ESD-compliant work sandal**

The perfect companion to brighten up your workday. SUN OB has an open design that is extra breathable and comfortable, making both sweaty and sore feet a thing of the past. This slip-on shoe offers ESD protection and has a slip-resistant outsole that prevents slips, trips and falls. Made with lightweight and vegan materials.


Upper	Synthetic Leather
Lining	N/A
Footbed	SJ foam footbed
Outsole	PU
Category	OB / SRC
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.199 kg
Norms	ASTM F3445:2021 EN ISO 20347:2012




BLK




WHT

**Breathable upper**  
Increased moisture and temperature management for extended wearer comfort.



**SRC slip resistance**  
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



**Removable insole**  
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



**Vegan**  
Uses or contains no animal products.



### Solutions for every workplace

INDUSTRIAL   PROFESSIONAL   TACTICAL   TIGER GRIP

ENGINEERED IN EUROPE

www.safetyjogger.com

**Industries:**

Cleaning, Medical, Food &amp; beverages, Assembly

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Synthetic Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	1.92	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	18	≥ 15
<b>Lining</b>	<b>N/A</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	N/A	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	N/A	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>PU</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	140	≤ 150
	Outsole slip resistance SRA: heel	friction	0.42	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.39	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	32	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.