



Heavy

X430 EH SB

X430EH

Mid-cut safety shoe with heat-resistant outsole and EH protection

Safety Jogger X430EH high-cut safety shoes offer top-notch EH protection, SR-tested soles, and heat resistance up to 300°C. They're cold insulated, waterproof, and metal-free for superior comfort and versatility.

Upper	Leather
Lining	Membrane
Footbed	SJ foam footbed
Midssole	Textile
Outsole	PU/Rubber
Toecap	Composite
Category	SB / P (Composite), WR, E, CI, FO, HRO, SRC
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.780 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK



Waterproof (WR)

Waterproof footwear prevents liquids to enter into the shoe.



DGUV BGR 191

These shoes are suitable for orthopedic insoles and orthopedic alterations. Certified according to BGR 191.



Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.




Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Cold insulated (CI)

Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

Industries:

Automotive, Chemical, Cleaning, Construction, Logistics, Mining, Oil & Gas

Environments:

Dry environment, Wet environment, Warm surfaces, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Leather			
	Upper: permeability to water vapor	mg/cm ² /h	4.84	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	45	≥ 15
Lining	Membrane			
	Lining: permeability to water vapor	mg/cm ² /h	2.6	≥ 2
	Lining: water vapor coefficient	mg/cm ²	24.3	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	85	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.42	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.15	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.24	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	34	≥ 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	17.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	22.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.